



engine drive **powerblast** sprayer

single **38"** diameter fan

length	21'
height	63"-70" to fan housing/adjustable
width	100" (21.5L-16.1/adjustable axle)
tire options	16.5L-16.1 rib or terra 21.5L-16.1 rib or terra 11.25-24 rib
axle options	multiposition adjustable fixed offset (specify)

John Deere <i>Powertech</i> 4.5L diesel engine 115 horsepower Tier III turbocharged	38" diameter 9 blade stainless steel axial flow fan operating @2200RPM
Electric throttle	SS304 stainless steel blower housing
Vibration dampener on flywheel minimizes drivetrain vibration	Electric fan clutch
Large surface easy clean radiator	Lower air scoops
50 gallon fuel capacity	500 gallon stainless steel tank stainless steel plumbing, lid assembly
Safety shut down system	stainless steel large paddle mechanical agitation stainless steel tank rails, engine shroud
Oil pressure	
Water temperature	2" NPT Quick-Fill fittings front & rear of tank
Control from the cab	Rears RPA centrifugal pump 80GPM/200PSI
Throttle	
Spray manifold	
Dump valve	Electric pump clutch
Emergency Shut Down	Electric spray controls
Cab mounted instrumentation	Electric dump valve
Tachometer	
Oil pressure	
Water temperature	Suction and discharge line strainers are easily isolated for cleaning during operation
Fuel level	Dual pressure strainers
Hour meter	Oversize suction line strainer with large surface area screen element and stainless steel housing
Air cleaner service indicator	
Programmable throttle settings	
Work Lights	Rollover nozzles with ceramic tips Diaphragm check valves on each nozzle for positive shut-off
	Adjustable swivel hitch

**For more information,
or the location of your nearest dealer,
please call 800.547.8925**

